

# RACK MODE STORAGE BATTERY

- 2-15 units can be used in parallel
- Convenient to PLUG IN/OUT
- 6000 cycles life
- Precise Battery Management Technology
- High-density LiFePO4 battery, safer to use
- Possess industry-leading BMS technology
- Compatible with mainstream inverters
- DOD 80% ,extend battery life

ZC-L · 51100



Stable Power Supply



Precise Management



High Utilization



Long Life Cycle

## Model

ZC-L 51100

### Basic Information

Nominal Voltage	51.2V DC
Voltage Range	44V-58.4V
Nominal Capacity	100Ah
Rated Capacity	5.12kWh
Communication Protocol	CAN / RS485 / RS232
Max. Number of Parallel Connections	15
Cycle Life	6000 cycles (@80% DoD)
Protection Mechanism	Temperature Protection/Over-current Protection/Short-circuit Protection Over-charge Protection/Over-discharge Protection/Low-voltage Protection

### Charging Parameters

Recommended Charging Current	50A
Max. Charging Current	100A
Recommended Charging Voltage	58V
Max. Charging Voltage	58.4V

### Discharging Parameters

Recommended Discharging Current	50A
Max. Discharging Current	100A
Recommended Battery Discharge Cut-off Voltage	46V
Battery Cut-off Voltage	44V
Battery Recovery Voltage	48V

### General Parameters

Dimension	500*484*178mm
Gross/Net Weight	46kg/43.5kg
Shell Material	Sheet Metal
Protection Rating	IP20
Installation Method	Rack Mode
Cell Type	LiFePO4

### Certification & Safety Standard

Safety Certification	CE
Transportation Safety Certification	UN38.3,Class9

### Temperature Parameters

Discharging Temperature	-20~60°C
Charging Temperature	0~55°C
Storage Temperature	-20~45°C